


CSD 3324E



Secure Telecommunications

Secure Applications

- Secure Digital Voice
- Fax Encryption
- Data Encryption

Features

- Exceptional voice quality with speaker recognition
- Automatically adjusts for poor quality phone lines
- Two-wire fax interface provides universal group 3 fax encryption
- Automatic voice/fax select
- Strategic, long term security
- Automated electronic key management
- Installation and operation training accomplished in minutes

Product Overview

The CSD 3324E is a comprehensive office communications security system that provides voice, fax and data encryption in an executive telephone package. Your most sensitive information is protected by TCC's high grade encryption and automated key management system. Internal storage of 400 keys coupled with automatic key changes provides complete hands-off security.

Superior voice quality is achieved by two integrated vocoders. The CSD 3324E actually reduces noise and hiss in poor quality phone lines. Fax encryption is interfaced at the two-wire phone line to allow group 3 fax encryption regardless of what brand of fax is used. Additionally, an RS-232 port allows a PC or other data device to be connected to the CSD 3324E for secure data transmissions.

Granite Island Group
127 Eastern Avenue, #291
Gloucester, MA 01931
(978) 546-3803
<http://www.tscm.com/>

Granite Island Group - <http://www.tscm.com/>

CSD 3324E

Technical Specifications

Encryption Algorithm

TCC proprietary Teltect™
non-linear key generator

Crypto Key Variables

System Key: 1.16×10^{77}
Network Key: 1.84×10^{19}
Local Key: 1.84×10^{19}
Total Keys: 3.93×10^{115}

Key Storage

400 Local Keys stored in two
keybanks containing 200 keys

Key Loading

SmartModule™ keyfill device
or keypad entry

Vocoders

9600 bps Multi-Pulse
4800 bps CELP

Data Modems

CCITT V.32: 9600 to 4800 bps
CCITT V.22: 2400 to 600 bps

Fax Modems

CCITT V.29
CCITT V.27/ter

Telephone Interface

2-wire, RJ-11C connector

Fax Interface

2-wire, RJ-11C connector

Data Interface

25-pin EIA-RS-232D



Operating Modes

Autosense voice/fax
Autosense voice/data
Fax only

Size and Weight

12" by 10" by 2"
(30cm x 25cm by 5cm)
9 lbs (4.1 kg)

Environmental

Operating Temperature:
0°C to 50°C
Relative Humidity:
10% to 90%

Power

115 VAC, 60Hz - or -
230 VAC, 50Hz - or -
10-30 VDC


Power Consumption

Maximum 7 watts

Options and Accessories

SmartModule keyfill device
115/230VAC Switchable Power
Portable Briefcase Model
Briefcase Model with Fax
Briefcase Model with PC

SmartModule and Teltect are trademarks of
Technical Communications Corporation.



TCC's SmartModule keyfill device



Granite Island Group
127 Eastern Avenue, #291
Gloucester, MA 01931
(978) 546-3803
<http://www.tscm.com/>